




BL-362-C



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Description:

The BL-362-C is a Continuous Gripstay Channel for use on backup block. Accepts any Gripstay Anchor for masonry or stone.

Sheet Metal (Carbon Steel):

ASTM A 366

Zinc Coating:

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).

Note: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Sheet Metal (Stainless Steel):

ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors) (Type 316 available on special order).

Note: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Dimensions:

Thickness: 14 gauge, 12 gauge, or 11 gauge

Length: 5'0", other lengths available in 7 1/2" increments

Hole size: 5/16"

Finishes:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel: ASTM A 580 - AISI Type 304 (Type 316 available on special order).

Thickness:

- 14 gauge
- 12 gauge
- 11 gauge

Length:

- Standard 5'0"
- 15" 22 1/2" 30"
- 37 1/2" 45" 52 1/2"