



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Description:

The BL-363 Flexible Gripstay Anchor permits horizontal and vertical movement of the masonry wall while restraining the wall from moving laterally out of plane.

Wire (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:
Tensile Strength - 80,000 p.s.i.
Yield Point - 70,000 p.s.i. minimum

Zinc Coating:

Hot-dip galvanized after fabrication ASTM A 153 (1.5 oz/ft²)

Note: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Wire (Stainless Steel):

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

Sheet Metal (Carbon Steel):

ASTM A 366

Zinc Coating:

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).

Note: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Sheet Metal (Stainless Steel):

ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors)(Type 316 available on special order).

Finishes:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel: ASTM A 580 - AISI Type 304 (Type 316 available on special order).

Note: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Gripstay Head Thickness:

- 14 gauge
- 12 gauge

Vee Wall Tie Length: 3/16" dia

- | | | | |
|-----------------------------|---------------------------------|-----------------------------|--------------------------------------|
| <input type="checkbox"/> 3" | <input type="checkbox"/> 3 1/2" | <input type="checkbox"/> 4" | <input type="checkbox"/> 4 1/2" |
| <input type="checkbox"/> 5" | <input type="checkbox"/> 7" | <input type="checkbox"/> 9" | <input type="checkbox"/> Other _____ |

Vee Wall Tie portion manufactured from a minimum of 95% post-consumer recycled material.