



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

BL-303 Corrugated Dovetail Brick Tie

For anchoring masonry to concrete with 305 Dovetail Slot.
Standard - 1" wide x 16ga., 14 ga., or 12 ga. thick, by 3 1/2" or 5 1/2" long.
Other lengths available upon request.

Sheet Metal (Carbon Steel):

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).
Blok-Lok will certify to a minimum of 2.0 oz/ft².

Sheet Metal (Stainless Steel):

ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors) (Type 316 available on special order).
NOTE: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Blok-Lok is not responsible for incompatibility if ties or slots are interchanged with those of other manufacturers.

Finishes:

- Hot-Dip Galvanized (ASTM A 185)
- Stainless Steel (ASTM E 437, Type 304)

Anchor Thickness:

- 16 gauge
- 14 gauge
- 12 gauge

Length:

- 3 1/2" 5 1/2" Other _____

Dovetail Slot Thickness:

- 24 gauge
- 22 gauge
- 18 gauge
- 16 gauge