



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

**Wire (Carbon Steel):**

Cold-drawn steel wire conforming to ASTM A 82:  
 Tensile Strength - 80,000 p.s.i.  
 Yield Point - 70,000 p.s.i. minimum  
 Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft<sup>2</sup>)  
 Blok-Lok will certify to a minimum of 2.0 oz/ft<sup>2</sup>.

**Wire (Stainless Steel):**

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

**Sheet Metal (Carbon Steel):**

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).  
 Blok-Lok will certify to a minimum of 2.0 oz/ft<sup>2</sup>.

**Sheet Metal (Stainless Steel):**

ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors)(Type 316 available on special order).  
 NOTE: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

**BL-303-SV** is 1" wide x 14 ga., 12 ga., or 11 ga., and is available in any length.

**Finishes:**

- Hot-Dip Galvanized (ASTM A 185)
- Stainless Steel (ASTM E 437, Type 304)(316 available on special order)

**Thickness:**

- 14 gauge
- 12 gauge
- 11 gauge

**Length:** \_\_\_\_\_

**Continuous Wire:**

- 9 gauge
- 3/16"Ø

Blok-Lok is not responsible for incompatibility if ties or slots are interchanged with those of other manufacturers.