



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

BLT-8

BLT-8 Flex-O-Lok® Tie is a flexible tie for tying masonry to concrete with a dovetail slot. Provides lateral restraint while permitting horizontal and vertical movement.

Dimensions:

3/16" (4.76 mm) diameter wire x 3 1/2" (88.9 mm), 4 1/2" (114.3 mm), 5 1/2" (139.7 mm), 7 1/2" (190.5mm), 9 1/2" (241.3mm) long

Sheet Metal: 12 gauge

Carbon Steel ASTM A 366

Zinc Coating - ASTM A 153 Class B (sheet metal ties and anchors dipped after fabrication).

Stainless Steel ASTM A 167 - AISI Type 304 Stainless Steel

Wire:

3/16" (4.76 mm) Diameter Wire

Carbon Steel per ASTM A 82, Hot-Dip Galvanized per ASTM A153, C1 B2

Stainless Steel per ASTM A580

Packaging:

100 pieces per box

Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.

Finish:

- Hot-Dip Galvanized per ASTM A153, C1 B2
- Stainless Steel Type 304 per ASTM 167

Note: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Length:

- 3 1/2"
- 4 1/2"
- 5 1/2"
- 7 1/2"
- 9 1/2"

Seismic Tie

Note: Blok-Lok is not responsible for incompatibility if ties or slots are interchanged with those of other manufacturers.