



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

BLT-9A web tie is available to accommodate various wall widths. Use with adjustable Flex-O-Lok® Anchors.

Dimensions:

3/16" (4.76 mm) diameter x 12" (303 mm) long x 2 3/8" (60 mm), 4" (100mm), 6" (152mm), 8" (203 mm), or 10" (254 mm) wide.

Wire: (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:

Tensile strength - 80,000 p.s.i.

Yield Point - 70,000 p.s.i. minimum

Zinc Coating: Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)

Wire: (Stainless Steel):

ASTM A 580 - AISI Type 304. (Type 316 available on special order.)

Packaging:

250 pieces per box

Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.

Finishes:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel Type 304

Width:

- 2 3/8" (60 mm)
- 4" (100 mm)
- 6" (152 mm)
- 8" (203 mm)
- 10" (254 mm)