



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

**Sheet Metal (Carbon Steel):**  
ASTM A 366/A (Cold-rolled)  
ASTM A 569 (Hot-rolled, pickled and oiled)

**Finishes - Sheet metal (Carbon-Steel):**  
Mill Galvanized - ASTM A 653 Coating Designation G60  
Hot-Dip Galvanized - ASTM A 153 class B (sheet metal ties and anchors hot-dip galvanized after fabrication).  
Note: Blok-Lok will certify to a minimum zinc coating of 2.0 oz./ft.<sup>2</sup>

**Sheet Metal (Stainless Steel):**  
ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors) (Type 316 available on special order)  
Note: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

**Finishes:**

- Mill Galvanized
- Hot-Dip galvanized
- Stainless Steel

**Size:** 12 ga. x block size, with 2 1/2" bends

- |                              |                              |                             |
|------------------------------|------------------------------|-----------------------------|
| <input type="checkbox"/> 4"  | <input type="checkbox"/> 6"  | <input type="checkbox"/> 8" |
| <input type="checkbox"/> 10" | <input type="checkbox"/> 12" |                             |

**Note:**

- NS-Neoprene Sponge also available. Submittal sheet available on request.
- Other sizes available for heavy-duty applications
- Complies with CSA A370-04