



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Wire (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:
Tensile Strength - 80,000 p.s.i.
Yield Point - 70,000 p.s.i. minimum

Wire (Stainless Steel):

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

Screw:

ASTM C 954 (1000-hour polymer coating)

NOTE:

U.S. Patent No. 8,037,653
Canadian Patent No. 2,690,819

Finish:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel: ASTM A 580 - AISI Type 304 (Type 316 available on special order).

2-Seal Tie Style:

- 2-Seal Tie (5/8")
- 2-Seal Tie (1")
- 2-Seal Tie (1 1/2")
- 2-Seal Tie (2")
- 2-Seal Tie (2 1/2")
- 2-Seal Tie (3")
- 2-Seal Tie (3 1/2")

Note: Length includes insulation and wallboard total thickness.

2-Seal Byna-Lok Tie: 3/16"Ø x length

- | | |
|-----------------------------|---------------------------------------|
| <input type="checkbox"/> 3" | <input type="checkbox"/> 5" |
| <input type="checkbox"/> 4" | <input type="checkbox"/> Custom _____ |