



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

**Wire (Carbon Steel):**

Cold-drawn steel wire conforming to ASTM A 82:  
Tensile Strength - 80,000 p.s.i.  
Yield Point - 70,000 p.s.i. minimum  
Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft<sup>2</sup>)  
Blok-Lok will certify to a minimum of 2.0 oz/ft<sup>2</sup>.

**Wire (Stainless Steel):**

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

**Sheet Metal (Carbon Steel):**

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).  
Blok-Lok will certify to a minimum of 2.0 oz/ft<sup>2</sup>.

**Sheet Metal (Stainless Steel):**

ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors)(Type 316 available on special order).  
NOTE: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

**Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.**

**Finishes:**

- Hot-Dip Galvanized (ASTM A 185)
- Stainless Steel (ASTM E 437, Type 304)

**Thickness:**

- 14 gauge
- 12 gauge

**Byna-Lok:** 3/16" dia. x

- 3"       4"       5"

**Continuous Wire:** system includes heavy-duty continuous wire.

**Blok-Lok is not responsible for incompatibility if ties or slots are interchanged with those of other manufacturers.**