


BYNA-LOK™ PROFILE



UPWARD PITCH
FRONT LEG

UPWARD PITCH
REAR LEG

Swaged to accept
continuous wire.



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

A masonry veneer can be anchored to studs, existing masonry, concrete or steel with the Byna-Lok™ Wire Tie. Various Blok-Lok Anchor systems can be fitted with the Byna-Lok™ Wire Tie, affording easy and secure insertion of the continuous joint reinforcing wire. Masonry veneer walls are then reinforced with continuous wire.

Wire: (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:

Tensile Strength - 80,000 p.s.i.

Yield Point - 70,000 p.s.i. minimum

Zinc Coating:

Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)

Wire: (Stainless Steel):

ASTM A 580 - AISI Type 304. (Type 316 available on special order.)

Wire Diameter:

3/16" (4.76 mm)

Finishes:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel: Type 304 ASTM A 580

Byna-Lok™ Length:

- 3"
- 4"
- 5"

Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.