



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Flex-Flash™ Flashing

Flex-Flash™ has a pressure-sensitive, clear adhesive that will not drool when exposed to UV or heat. Flex-Flash™ is a 40-mil thick membrane formulated with Elvaloy® Kee.*

- Extremely tough, with excellent impact and tear resistance.
- Flexibility is maintained in all weather environments, even in extreme heat or cold.
- Highly resistant to oils and will repel most chemicals.
- Compatible with most silicone and urethane sealants.
- Suitable for thru-wall or surface-mount applications.
- Pre-formed corners and end dams available upon request.
- Not susceptible to degradation by UV.

Flex-Flash™ conforms to: ASTM D412-99a, ASTM D2240-00, ASTM D624-00 Die C and ASTM G154-00a.

U.S. Pat. No. 6,584,746 Other Patents Pending

*Elvaloy is a registered trademark of the DuPont Company

Standard Widths:

- Rolls are 75 ft. long

- | | |
|------------------------------|------------------------------|
| <input type="checkbox"/> 12" | <input type="checkbox"/> 20" |
| <input type="checkbox"/> 16" | <input type="checkbox"/> 24" |
| <input type="checkbox"/> 18" | <input type="checkbox"/> 36" |

Corners:

- | | |
|-----------------------------------|----------------------------------|
| <input type="checkbox"/> Inside | <input type="checkbox"/> Outside |
| <input type="checkbox"/> End Dams | |

DP - Drip Plate (Optional):

- | | | |
|-------------------------------|-----------------------------|--------------------------------------|
| <input type="checkbox"/> 1 ½" | <input type="checkbox"/> 3" | <input type="checkbox"/> Other _____ |
|-------------------------------|-----------------------------|--------------------------------------|

Required for Surface-Mount Applications:

- | |
|--|
| <input type="checkbox"/> Termination Bar |
| <input type="checkbox"/> Foam Tak™ Spray adhesive (12 oz. can) |

Note: Contact the Blok-Lok technical department for complete storage and installation information. A sealant compatibility chart is available at blok-lok.com