



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

The BLT-10 is a hook-on type tie, available in two types, for tying masonry walls to structural steel. Can be spot welded to steel after installation.

Wire: (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:

Tensile Strength - 80,000 p.s.i.

Yield Point - 70,000 p.s.i. minimum

Zinc Coating:

Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)

Wire: (Stainless Steel):

ASTM A 580 - AISI Type 304. (Type 316 available on special order.)

Packaging:

250 pieces per box

Blok-Lok manufactures steel wire products from a minimum of 95% post-consumer recycled material.

Finishes:

- Hot-Dip Galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)
- Stainless Steel: Type 304 ASTM A 580

Type A Length:

- 3" (76 mm)
- 5" (127 mm)
- 7" (178 mm)
- 9" (228 mm)

Type B Length:

- 10" (254 mm)
- 12" (355 mm)
- 14" (178 mm)
- 16" (406 mm)

Wire Diameter:

- 3/16" (4.76 mm)
- 1/4" (6.35 mm)