



DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Wire (Carbon Steel):

Cold-drawn steel wire conforming to ASTM A 82:

Tensile Strength - 80,000 p.s.i.

Yield Point - 70,000 p.s.i. minimum

Zinc Coating:

Hot-dip galvanized after fabrication: ASTM A 153 (1.5 oz/ft²)

NOTE: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Wire (Stainless Steel):

ASTM A 580 - AISI Type 304 (Type 316 available on special order)

Sheet Metal (Carbon Steel):

ASTM A 366

Zinc Coating:

ASTM A 153 Class B (sheet metal ties and anchors hot-dip galvanized after fabrication).

NOTE: Blok-Lok will certify to a minimum of 2.0 oz/ft²

Sheet Metal (Stainless Steel):

ASTM A 666, ASTM A 480, ASTM A 240, ASTM A 167 - AISI Type 304 Stainless Steel (sheet metal ties and anchors)(Type 316 available on special order).

NOTE: Blok-Lok recommends Stainless Steel for maximum protection against corrosion.

Patents Pending

BL-200X Backplate

Style **Insulation Thickness**

- | | | |
|--------------------------|----------------|------|
| <input type="checkbox"/> | BL-200X (0") | 0" |
| <input type="checkbox"/> | BL-200X (1") | 1" |
| <input type="checkbox"/> | BL-200X (1 ½") | 1 ½" |
| <input type="checkbox"/> | BL-200X (2") | 2" |
| <input type="checkbox"/> | BL-200X (2 ½") | 2 ½" |
| <input type="checkbox"/> | BL-200X (3") | 3" |
| <input type="checkbox"/> | BL-200X (3 ½") | 3 ½" |

Thickness:

- 14 Gauge
- 12 Gauge

3/16"Ø Pintle Length:

- 3"
- 4"
- 4 ¾"
- 5 ¼"
- Custom _____

Finish:

- Hot-Dip Galvanized
- Stainless Steel