



HOHMANN & BARNARD'S TEXTROFLASH™ PRIMER-36

MATERIAL SAFETY DATA SHEET

SECTION I. PRODUCT IDENTIFICATION

PRODUCT CODE: Textroflash™ Primer-36
PRODUCT NAME: Polymer Modified Adhesive Emulsion Coating

SECTION II. INGREDIENT INFORMATION

	%	CAS	TLV
Acrylic Polymers	35-45	Proprietary Blend	NA
Water	65-55	7732-18-5	NA

This product does not contain any materials listed by OSHA, NTP, or IARC as carcinogens.

SECTION III. HEALTH HAZARD INFORMATION

CAUTION! HEATING MAY RELEASE HYDROGEN SULFIDE GAS (H₂S)

EYE CONTACT: The cool material will cause minor eye irritation. Signs and symptoms may include, pain, tears, swelling, redness and blurred vision.

SKIN CONTACT: Prolonged or repeat contact may cause moderate skin irritation to the point of vesiculation.

INHALATION: Prolonged or repeat exposure to vapors is a primary irritant to the nasal passages and the upper respiratory tract. If inhaled, this substance is considered practically non-toxic to internal organs.

INGESTION: This is an unlikely route of entry, however if swallowed, this substance will cause gastrointestinal irritation, nausea, vomiting and diarrhea.

FIRST AID

EYE CONTACT: Flush eyes, including under eyelids, with clear, running lukewarm water for at least fifteen minutes. Get medical attention.

SKIN CONTACT: Removing contaminated clothing. Wash affected areas with soap and water. Get medical attention if irritation persists.

HMS RATING:

HEALTH - 2

FIRE - 1

REACTIVITY - 0

PERSONAL PROTECTION - B Slightly toxic moderate hazard stable safety glasses, gloves

SECTION IV. FIRE AND EXPLOSION DATA

FLASH POINT AND METHOD:	Not Available
UPPER EXPLOSIVE LIMIT:	Not Available
LOWER EXPLOSIVE LIMIT:	Not Available

EXTINGUISHING MEDIA: Water, carbon dioxide and dry chemical. Use water spray to cool fire-exposed containers. A fine water mist may be used to smother fire or to disperse vapors. Do not use a solid

stream of water since the stream will scatter and spread the fire. Fire fighters must wear self-contained breathing apparatus and full protective clothing when fighting fires involving this material.

SECTION V. REACTIVITY DATA

STABILITY: Normally stable as defined in NEPA 704-12 (4-3.1)

INCOMPATIBILITY: Cationic Agent

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

CONDITIONS TO AVOID: Do not store near heat.

SECTION VI. PHYSICAL DATA

BOILING POINT: -100 °C

APPEARANCE AND ODOR: Liquid with characteristic odor

SPECIFIC GRAVITY: 1.02

SECTION VII. SPILL, LEAK, AND DISPOSAL PROCEDURE

Notify safety personnel of large spills or leaks. Clean-up personnel need protection against liquid contact and vapor inhalation. Absorb small spills and collect liquid, if feasible, or absorb with vermiculite or sand. Do not flush to sewer or stream. Dispose of liquid waste via licensed waste disposal company. Follow Federal, State and Local regulation.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Wear impervious gloves and safety glasses to prevent contact with the skin and eyes. If repeated or prolonged contact with liquid is likely, wear protective clothing including boots, apron, and faceshield or splash goggles. Remove contaminated clothing immediately and do not reuse until it has been properly laundered. Eye wash stations and safety showers should be available in use and handling areas. Contact lenses pose a special hazard; soft lenses may absorb and all lenses concentrate irritants.

SECTION IX. SPECIAL PRECAUTIONS AND COMMENTS

Store in closed containers in a cool, dry, well-ventilated area away from oxidizers, heat and open flame. Protect container from physical damage.

Date Prepared: 1/07/08 Revision: 0